

Section 1: Identification of the Material and Supplier

1.1 Product identifier

- Product Name: FASLOC® Resin Capsules
- Synonyms: FASLOC® Resin Cartridges, FASLOC® Dual Speed Capsules, FASLOC® Spin to Stall Resin Capsules

1.2 Uses and uses advised against

- Application: Resin based Anchor System for roof support in mining
- Compliance: Manufactured to the requirements of SANS 1534:2018 "Resin Capsules for use with tendon based support systems".

1.3 Details of the supplier of the product

- Company: ROCBOLT Technologies (Pty) Ltd
- Address: 30 North Reef Road, Gremiston, 1429
- Telephone: +27 (0)11 8786800
- Fax: +27 (0)11 8786811
- Website: www.rocbolt.com

1.4 Emergency telephone numbers

- Emergency Telephone (o/h): +27 (0)11 8786800
- Emergency Telephone (a/h): +27 (0)76 8912707 (06:00-22:00 GMT+2)

Section 2: Hazards Identification

2.1 Classification of the substance or mixture

Health Hazards

- Skin Irritation: Category 2
- Eye Irritation: Category 2A
- Toxic to Reproduction: Category 2
- Specific Target Organ Toxicity: Category 2
- (Repeated Exposure): Category 2

2.2 GHS Label elements

- Signal Word
- Pictograms

WARNING



Hazard Statements

- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H361 Suspected of damaging fertility or the unborn child
- H373 May cause damage to organs through prolonged or repeated exposure

Prevention Statements

- P201 Obtain special instructions before use
- P202 Do not handle until all safety precautions have been read and understood
- P260 Do not breathe dust/fume/gas/mist/vapours/spray
- P264 Wash hands thoroughly after handling
- P280 Wear protective gloves/protective clothing/eye protection/face protection

Response Statements

- P302 + P352 IF ON SKIN: Wash with plenty of soap and water
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes
Remove contact lenses, if present and easy to do. Continue rinsing
- P308 + P313 If exposed or concerned: Get medical advice/attention
- P321 Specific treatment is advised - see first aid instructions
- P362 Take off contaminated clothing and wash before re-use

Disposal Statements

- P501 Dispose of contents/container in accordance with relevant regulations

2.3 Other hazards

The materials contained in this product may only represent a hazard if the integrity of the packaging is compromised. If the capsule packaging compromised (e.g. leaks/splits), the product may cause an allergic skin reaction, skin irritation and severe eye irritation if in contact with the substance.

The product is flammable, although the risk of ignition is very low.

Section 3: Composition/Information on Ingredients

3.1 Product description

Resin and catalyst mastic containing inert fillers, separated, sealed and contained in a translucent plastic film.

Components	CAS Number	%WW
Polyester Resin	39459-88-6	<25[%]
Styrene	100-42-5	<10[%]
Other Material		Up to 100[%]

Section 4: First Aid Measures

4.1 Description of first aid measures

- Eye Contact: If in eyes, hold eyelids apart and flush continuously with running water. Flush for at least 15 minutes and seek medical attention.
- Inhalation: If inhaled, remove from contaminated area. To protect rescuer, use self-contained breathing apparatus. Apply artificial respiration if not breathing.
- Skin Contact: If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water and soap/suitable cleanser. Seek medical attention if irritation persists or symptoms of exposure develop.
- Ingestion: If swallowed, do not induce vomiting. Wash mouth with water. Obtain medical attention. Beware of aspiration should vomiting occur. Ingestion is considered unlikely due to product form.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

Section 5: Firefighting Measures

5.1 Extinguishing media

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture

Comustible paste. May evolve toxic gasses (carbon dioxides, styrene, hydrocarbons) when heated to decomposition. Styrene may polymerise readily at elevated temperatures and may violently rupture sealed containers.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved when heated. Wear full protective equipment including self-contained breathing apparatus (SCBA) when combatting fire. Use water spray to cool nearby containers and water fog for nearby storage areas.

Section 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in Section 8 of the SDS. Ventilate area where possible.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover/absorb spill with non-combustible absorbent material (vermiculite, sand or similar), collect and place in suitable containers for disposal. Eliminate all sources of ignition.

6.4 Reference to other sections

See Section 8 and 13 for exposure controls and disposal.

Section 7: Handling and Storage

7.1 Precautions for safe handling

Before use, carefully read the product label and markings. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage

Store in a cool, dry well ventilated area, removed from heat or ignition sources and foodstuffs. Ensure containers are adequately labeled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate ventilation and fire protection systems. Underground storage should be in return airway. For maximum quality, store at temperatures close to or just under 25[°C].

Section 8: Exposure Controls/Personal Protection

8.1 Controls

Use only in well ventilated areas.

8.2 Personal protection

In case of poor ventilation, wear suitable respiratory equipment. The use of impervious gloves, safety glasses and overalls are recommended.

Section 9: Physical and Chemical Properties

9.1 Info on basic physical and chemical properties

- Physical State:	Paste
- Colour:	Black/yellow paste with off-white or coloured catalyst
- Boiling Point:	145[°C]
- Flash Point:	> 30[°C] (Closed up)
- Relative Density:	2.0 at 20[°C]
- Water Solubility:	Insoluble

Section 10: Stability and Reactivity

10.1 Reactivity

Carefully review all information provided in Sections 10.2 to 10.6.

10.2 Chemical stability

Stable under normal recommended conditions of storage and use.

10.3 Possibility of hazardous reactions

Polymerises with the evolution of heat. Can enhance combustion of other materials.

10.4 Conditions to avoid

Do not mix with other chemicals or store in direct sunlight and extreme temperatures. Keep away from ignition sources and open flames.

10.5 Incompatible materials

Oxidising agents, strong acids, strong alkalis and accelerators.

10.6 Hazardous decomposition products

May evolve toxic gasses when heated to decomposition.

Section 11: Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity: Due to the product form (enclosed), contact with contents is not anticipated with normal use.

11.2 Information available for the ingredients

Styrene: LD50 oral > 5000[mg/kg] (rat), skin > 2000[mg/kg] (rat), inhalation 11.8[mg]/L/4 hours (rat).

Benzoyl Peroxide: LD50 oral 5700[mg/kg] (mouse), skin > 1000[mg/kg] (mammal).

- Skin: Due to product encapsulation, the potential for skin contact is reduced. If the container is damaged, contact may result in irritation, redness, pain, rash, dermatitis and possible burns. Effects may be delayed.
- Eye: Due to product encapsulation, the potential for eye contact with contents is reduced. If the container is damaged or splatter occurs, direct contact may result in irritation, lacrimation and burns.
- Sensitisation: Exposure to contents may cause skin sensitisation. This product is not classified as a respiratory sensitiser.
- Carcinogenicity: Due to the product encapsulation, exposure to contents is not anticipated with normal use. Styrene is classified as possibly carcinogenic to humans.
- Reproductive Toxicity: Due to the product encapsulation, exposure to contents is not anticipated with normal use. Styrene is suspected of damaging fertility or the unborn child.
- Aspiration: Not classified as causing aspiration.
- STOT - Single Exposure: Over exposure may result in irritation of the nose and throat, coughing, nausea, vomiting, dizziness and breathing difficulties.
- STOT - Repeated Exposure: Due to product encapsulation, the potential for exposure to the contents is reduced. May cause damage to organs (nasal epithelial and ear) through prolonged or repeated exposure to styrene if inhaled.
- Mutagenicity: Insufficient data available to classify as a mutagen.

Section 12: Ecological Information

12.1 Toxicity

Harmful to aquatic organisms, avoid contaminating waterways.

- Styrene: LC50: 4.02[mg/l], Exposure time: 96[h], Species: Pimephales promelas (Fathead Minnow), flow-through test.
EC50: 4.7[mg/l], Exposure time: 48[h], Species: Daphnia magna (Water Flea), flow-through test.
EC50: 4.9[mg/l], Exposure time: 72[h], Species: Selenastrum capricornutum (Algae).

Section 13: Disposal Considerations

13.1 Waste treatment methods

- Waste Disposal: Dispose of in compliance of national legislation and local bylaws. Use of a registered waste disposal company is advised.

Section 14: Transport Information

No special transport arrangements are required.

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislations specific for the substance or mixture

- EC Directives: Dangerous substances directive 67/548/EEC.
Dangerous preparations directive 88/379/EEC.
- Statutory Instruments: OHS Act No 85 of 1993 and Regulations.
Mine Health and Safety Act No 29 of 1996 and Regulations.
Hazardous Substances Act, 1973 (Act No. 107 of 1998).
SANS 10234:2008 Globally Harmonised System of Classification and Labelling of Chemicals (GHS).

Section 16: Other Information

16.1 Additional information

The data and advice given in this document apply when the product is used for the stated purpose or application. The product is not suitable for any other application, and use of this product for any other application may give rise to risks not covered in this document. If in doubt as to the intended application, or use in other applications is considered, the advice of ROCBOLT Technologies (Pty) Ltd should first be sought.

If the product has been purchased for supply to a third party, it is the purchaser's duty to ensure that any person handling or using the product is provided with the information in this document.

It is the responsibility and duty of the employer to inform employees (or others who may be affected) of the hazards described in this document and the precautions that should be taken.

This document does not constitute or substitute for the users own assessment of workplace risk as required by other health and safety legislation.